



TruFLOW™

Manifold System

For years, Wirsbo has offered proven and reliable brass manifolds that contractors have come to depend on. Now, we offer a manifold with flow and temperature intelligence for radiant systems.



No assembly required – these high-quality brass manifolds, come out of the box and mount on the wall in a flash.

TruFLOW
MANIFOLD SYSTEM



Features

- Highly reliable extruded brass manifold system
- Pre-assembled 2 through 12-loop configurations with:
 - Basic end cap and end cap with vent and drain
 - R32 unions to accommodate any current manifold adapters
 - Heavy duty bracket off-set (front-to-back and side-to-side)
 - Wirsbo exclusive state-of-the-art electronic flow and temperature nipples (optional: for use with the Wirsbo Flow Master, sold separately)
- 1½" I.D. for superior flow characteristics
- Calibrated balancing valves on supply
- On/off valves on return
- Full line of accessories, including Manifold Extension Kit

Benefits

- High-flow capacity
- Loop isolation capability with more accurate balancing
- Electronic balancing system reading both temperature and flow per loop
- Easy balancing or trouble shooting
- Reliable solid body with o-ring seals
- Fast, easy and professional installation (no assembly required)
- Easy add-on Manifold Extension Kit for jobsite surprises
- Wirsbo exclusive design

RADIANT FLOORS
COMFORT HEATING





Wirsbo Electronic Balancing System features:

- Unique electronic nipples that read flow and temperature
- The Wirsbo Flow Master – a hand-held electronic read-out instrument
- Flow and temperature information stored for up to 12 manifolds
- Downloadable information for records
- Flow and temperature reading for each loop for accurate and quick balancing or troubleshooting
- Flow readings between 0.025 – 1.3 gpm (standard model)
- Flow readings between 0.53 – 1.85 gpm (high-flow model sold separately, available Summer 2003)



Wirsbo TruFLOW Manifold Extension Kit

The Extension Kit is designed for easy in-line extension of up to two additional loops for the Wirsbo TruFLOW Manifold System.

Consists of:

- Two-loop Supply Manifold with balancing valves
- Two-loop Return Manifold with on/off valves
- Electronic flow and temperature nipples
- 1¼" BSP x 1¼" BSP manifold unions
- R20 loop caps



Contact your local Wirsbo wholesaler for pricing and availability.

If you could build a radiant manifold from scratch, this would be it. The Wirsbo TruFLOW Manifolds look great on the wall and reduces your installation time.



Uponor Wirsbo
5925 148th STREET WEST
APPLE VALLEY, MN 55124

TEL: 800-321-4739
FAX: 952-891-1409
www.wirsbo.com

Copyright © 2003 Uponor Wirsbo, Printed in the United States



CS_TFM03/03